

AIRCRAFT GROUND POWER UNITS



TRAILER MOUNTED MODELS TM-4900/TM 4900-JD







Stewart & Stevenson electrical ground power units are available in either trailer, truck or tow-tractor mounted models, ranging from 37½ KVA to 200 KVA. Also available are Air Start units ranging from 120 PPM to 400 PPM and Tow Tractors in both Diesel and electric driven configurations, ranging from 16,000 to 100,000 lbs. GVW. Stewart & Stevenson backs it's equipment with complete Parts and Service Responsibility around the clock, anywhere in the world.

Specifications

GENERATOR	ENGINE	Model TM-4900	Model TM-4900-JD
Type Brushless	Make	G.M. Diesel	John Deere
K.V.A90	Туре	2 Cycle	4 Cycle
Volts	Number Cylinders	4	6
Phase	Bore	41/4"	4.9"
Frequency400 hertz	Stroke	5"	4.33"
RPM	Governor	Hydraulic	Electro Mechanical
Exciter Brushless	Starting Motor	12 Volt Delco	12 Volt
Overload 25% over rated output	Generator	12 Volt Delco	12 Volt
Frame Heavy Duty	Regulator	12 Volt Delco	12 Volt
	Length	102"	137"
	Width	66"	69"
	Height	67"	59"
	Weight	Approx. 5,000 Lbs.	Approx. 5,000 Lbs.

Electrical Characteristics

	Model TM-4900	Model TM-4900/TM 4900-JD
Voltage Regulation	Plus or minus 1% no-load to full load	Plus or minus 1% no-load to full load
Voltage Transient	Plus or minus 20%	Plus or minus 20%
Frequency Regulation	21/2% (10 cycles) no load to full load SG 1/4% (1 cycle) no load to full load PGS	Plus or minus 16 no load to full load
Frequency Transient	Plus or minus 3% no load to full load	
Voltage Modulation	0.5%	0.5%
Phase Balance	Not exceeding 1% at balanced level	Not exceeding 1% at balanced level
Line Drop	5% minimum compensation capacity	5% minimum compensation capacity

Standard Equipment*

Engine Thermostat Radiator & Fan Hydraulic governor Fuel Pump Electric Governor on TM 4900-JD Fuel Filters — primary & secondary Exhaust manifold & muffler Lube Oil Pump AC Generator (3 phase) Lube Oil Cooler All Engine and Generator controls & indicators Lube Oil Filters Starting motor and Alternator Jacket Water Pump Fuel Tank

Specifications subject to change without notice.

^{*}Optional and special equipment available on request.