

TAYLORTRUCK™



Power That Takes Charge!

MODEL	T-48	
TYPE	Electric	
SPEED (MAX MPH)	18	29 km/hr
RANGE (MILES)	30	48 km
LOAD CAPACITY (lbs)	3,000	1,363 kg
TOWING CAPACITY (lbs)	10,000	4,545 kg
BED SIZE (W"xL")	41x75	104x190 cm
VOLTAGE	48 Volt	
TURNING RADIUS (Inches)	145"	368 cm

Based on Standard Configuration

*Typical capacity: Actual load capacity depends on application and vehicle configuration



Tough and Dependable Product Solutions

Vehicles may be shown with optional equipment

Taylortruck™ is one of the first electric utility vehicles that can compete with gasoline vehicles performance in outdoor applications. This vehicle operates at 18 mph and can carry loads up to 3,000 lbs. Specifically designed to meet rugged outdoor applications, Taylortruck is equipped with a 48 volt drive train that travels up to 30 miles in a single charge.

Taylor-Dunn's GT Drive system provides hill climbing ability and acceleration while carrying heavy cargo during daily applications. Taylortruck standard features include load range E tires, durable unitized frame design, four wheel hydraulic brakes and regen braking that ensure reliability and low maintenance cost.

With performance that exceeds gasoline vehicles, and inherent cost benefits of electric vehicles, Taylortruck is the most cost effective solution to your utility needs. With products supported by a worldwide distribution system and trained sales staff, we can design a Taylortruck that meets your specific needs.

With more than 150,000 vehicles in service and over 50 years experience in providing solutions to our customers, Taylor-Dunn® products are the best way to go about your business.



TAYLOR-DUNN®

Commercial and Industrial Vehicles Since 1949

The best way to go about your business

PERSONNEL CARRIERS



Aristocrat



Roadmaster



Taylortruck



Loadmaster



Model B Series



Electruck



Maintenance Expediter



Stepsaver



Stockchaser

TOW TRACTORS



Towmaster



Mule




Pullmaster



Model E



Huskey



TAYLORTRUCK™ STANDARD SPECIFICATIONS

Product Line	MODEL B-T48
Unit Weight Lbs. (Kgs)	1900 (862 kgs)
Load Capacity Lbs. (Kgs)	3000 (1360 kgs)
Battery Type (Lead Acid)	8 Ea. 6V, 250 Amp Hr.
System Voltage	48V DC
Travel Distance	30 Miles 48.3 Km
Drive Axle	Automotive Type, Differential
Transmission	Oil Bath, Helical Gears, Single Speed
Motor	16.3 HP DC Separately Excited
Speed Unloaded	18 Mph 29 km/hr
Gradeability	10% Consult Factory
Tires	Pneumatic 20.5 x 8 x 10 Load Range E
Brakes	4 Wheel, Hydraulic Disc Standard, Hand Operated Parking Brake
Steering	24:1 Ratio Automotive Type
Wheels	4 Wheels
Frame	Unitized Fully Welded, Heavy Duty 14 GA Smooth Skin Steel
Bumper	Heavy Duty Steel Integrated Front & Rear Bumper
Suspension	Leaf Spring Front & Rear with Shock Absorbers, Coil Springs in Rear
Color	White
Seats	Split Seat Cushion with Full Length Back Rest Covered with Black Vinyl
Controller	Solid State Speed Controller
Wiring	Power Wiring & Battery Links 2 GA
Instrumentation	Smart View Display, Reverse Alarm, DC/DC Converter
Light Accessories	Dual Head Light & Dual Tail Light/Brake Light
Charger	25 Amp 48V Built In, Automatic with Interlock
Input Voltage	110/60 HZ.
Conformance Standards	Type E, ANSI B56.8, OSHA 1910.178

Specifications based on standard vehicle configuration on smooth level surface with unit unloaded.

TAYLORTRUCK™ OPTIONAL FEATURES

Charger

- Portable 25 amp charger or 40 amp charger
- Built in 110V/220V 50 Hz.

Accessories

- Strobe light, amber - on pole, or top of cab
- Directional signals

Deck

- Stake sides, removable end gate, 14" high
- 96 inch bed length (extended wheel base)
- Welding tank cutouts
- Steel sides and end gates, fold down
- Steel panel cargo box, with locking doors

Battery Compartment

- 244 a.h. batteries
- Lift out/roll out battery box
- 72 volt battery option
- Built in dual battery pack
- Battery watering system

Hitches

- Hitch automatic coupling, trailer
- Hitch pintle trailer
- Hitch, 1 7/8 ball and bracket

Cab

- Steel cab doors & safety glass windows
- Fiberglass cab & vinyl doors
- Mirrors - left, right and rear
- Windshield wiper

Top Frames

- Fiberglass or surrey top cover with tubular frame

Frame

- Fixed second seat, 2 passenger
- Fold down 2nd seat

Color

- Yellow, orange or special paint color
- Undercoating



TAYLOR-DUNN CORPORATION
Commercial and Industrial Vehicles Since 1949



2114 West Ball Road, Anaheim, CA 92804 • (714) 956-4040 • FAX (714) 956-3130
Toll Free (800) 688-8680 Visit our website: www.taylor-dunn.com