

Classic

**Model HTA (3,000 lb to 6,000 lb) Drawbar pull
(13.3 kN to 26.7 kN)**



Standard Features

- F-N-R shifter
- Keyless anti-restart ignition switch
- Two Headlights
- Combination Tail/Stop Lights & Back-up Light
- Volt Meter
- Water Temperature Gauge
- Engine Oil Pressure Gauge
- Engine Hour Meter Gauge
- Fuel Level Gauge
- Standard driver and passenger seat

Specifications For Model: CLASSIC 3,000 lb (13.3 kN) to 6,000 lb (26.7 kN) DBP

MODEL	HTA3o	HTA4o	HTA5o	HTA6o
DBP	3000 lbs (13.3 kN)	4000 lbs (17.8 kN)	5000 lbs (22.2 kN)	6000 lbs (26.7 kN)
Approx. GVW	4400 lbs (1995 kg)	5250 lbs (2381 kg)	6100 lbs (2767 kg)	7250 lbs (3289 kg)
Towed weight +/-	30000 lbs (13610 kg)	40000 lbs (18,140 kg)	50000 lbs (22680 kg)	60000 lbs (27220 kg)

Dimensions

Length	112" (2845 mm)
Width	55.5" (1410 mm)
Height	63" (1600 mm)
Height with cab	84" (2134 mm)
Wheel Base	70" (1778 mm)
Ground Clearance	8" (203 mm)
Turning Radius	120" (3048 mm)

Chassis

Drive Axle	Heavy-duty Harlan – 8200lb (3719 kg) load capacity
Steer Axle	Heavy-duty Harlan with 1 1/8" king pin
Suspension	Leaf Springs on front and rear axles
Towing Coupler	E-hitch with 1" Pin
Tires	Front: 6.50 x 10 Rear: LT215/85R x 16

Engine Options

Manufacturer - Diesel	Cummins, Perkins, Duetz
Manufacturer – Gasoline/LPG	GM, Zenith, Ford

Travel/Performance

Transmission	C-6 Automatic – 3 speeds forward 1 reverse (remanufactured)
Electrical	12 V Negative Ground
Cooling System	Liquid cooled radiator with integral transmission cooler
Steering System	Power assist
Service Brakes	Dual Split System, Hydraulic/Hydraulic, dual rear disc w/optional front brakes
Park Brake	Mechanical Drum – lever activated